

DATE: Monday, September 16, 2002

Set Name Query
side by side**Hit Count Set Name**
result set

DB=USPT,PGPB,JPAB,EPAB,DWPI,TDBD; PLUR=YES; OP=ADJ

L14	l12 and nozzle near (taper or contour)	2	L14
L13	L12 and (l10 or l11)	12	L13
L12	l9 and gas	167	L12
L11	L9 and (optic or fiber or mirror) near (tilt or pivot or rotary or rotate)	22	L11
L10	L9 and (optic or fiber or mirror) near (move or translate or lift or lower or raise)	6	L10
L9	L8 and (optic or fiber or mirror)	283	L9
L8	laser and (robot or robotic) and lens and nozzle	328	L8
L7	l6 and (capacitive or capacitor)near (sensor or detector or sense or detect)	2	L7
L6	(l3 or l5) and (capacitive or capacitor)	79	L6
L5	L2 and (mil or inch or micron or micrometer or mm or millimeter) near (height or distance or proximity or position or raise or lower or retract or extend)	90	L5
L4	L3 and (mil or inch or micron or micrometer or mm or millimeter) near (height or distance or proximity or position or raise or lower or retract or extend)	8	L4
L3	L2 and (stop or stopper or limit) near (height or distance or proximity or position or raise or lower or retract or extend)	71	L3
L2	L1 and (stop or stopper or limit)	727	L2
L1	laser and (robot or robotic) and lens and (determine or measure or sense or sensor or detect or detector) near (height or distance or proximity or position)	1027	L1

END OF SEARCH HISTORY